

Excellent Quality Pumps For Any Application



Amee[®]
WATER PUMPS



IS : 14220

IS : 8472



CM/L : 7660986 CM/L : 7660885



POWER GOLD - 2 / 2A / 1
(ALUMINIUM BODY)



POWER GOLD - 2
(C.I. BODY)

POWER GOLD SERIES... with ISI mark

Range : 0.5 HP(isi), 0.75 HP(isi), 1 HP(isi)
 Type : Self priming pump.
 Pipe size : 15 x 15 mm, 25 x 25 mm.
 Rpm : 2800 rpm.
 Head : upto 37 mtr.
 Suction : upto 8 mtr.
 Discharge : upto 40 lpm.
 Power supply : Single Phase

SUPER SERIES... with ISI mark

Range : 0.5 HP(isi), 1 HP(isi)
 Type : Self priming pump
 Pipe size : 25 x 25 mm.
 Rpm : 2800 rpm.
 Head : upto 45 mtr.
 Suction : upto 6 mtr.
 Discharge : upto 50 lpm.
 Power supply : Single Phase



SUPER-70 / 100 / 120
(ALUMINIUM BODY)



DELUXE - 70
0.5 HP



DELUXE - 70
0.5 HP

DELUXE-70 SERIES... with ISI mark

Range : 0.5 HP(isi)
 Type : Self priming pump.
 Pipe size : 15 x 15 mm.
 Rpm : 2800 rpm.
 Head : upto 30 mtr.
 Suction : upto 8 mtr.
 Discharge : upto 25 lpm.
 Power supply : Single Phase

DELUXE & V SERIES... with ISI mark

Range : 0.5 HP, 0.75 HP(isi) , 1HP(isi).
 Pipe size : 25 x 25 mm.
 Type : Self priming pump
 Rpm : 2800 rpm.
 Head : upto 50 mtr.
 Suction : upto 8 mtr.
 Discharge : upto 55 lpm.
 Power supply : Single & Three Phase



V SERIES
0.5 & 1 HP



DELUXE - 80
0.75 HP



DELUXE-90 / 100
0.75 & 1 HP



**ASM-1 CG
0.5 HP**



**ASM-3 CG
1 HP**

ASM CG SERIES...SINGLE PHASE with ISI mark

Range : 0.5 HP(isi), 0.75 HP, 1 HP (isi)
Type : Openwell Submersible pump.
Del. Pipe size : 25 mm.
Rpm : 2800 rpm.
Head : upto 31 mtr.
Discharge : upto 275 lpm.
Power supply : Single Phase.

****Available in Copper / Aluminium Rotor.**

ASM SERIES...SINGLE PHASE with ISI mark

Range : 0.5 HP(isi), 0.75 HP, 1 HP (isi) to 5 HP.
Type : Openwell Submersible pump.
Del. Pipe size : 25, 40, 50, 65, 75 mm.
Rpm : 2800 rpm.
Head : upto 36 mtr.
Discharge : upto 400 lpm.
Power supply : Single Phase.

****Available in Copper / Aluminium Rotor.**

****Available in Economy & Low voltage design.**



**ASM - 1
(SS BODY)**



**ASM - 2 to 8
(SS / MS BODY)**

ASM SERIES... THREE PHASE

Range : 1 HP to 15 HP.
Type : Openwell Submersible pump.
Del. Pipe size : 25, 40, 50, 65, 75, 100, 125 mm.
Rpm : 2800 rpm.
Head : upto 60 mtr.
Discharge : upto 4000 lpm.
Power supply : Three Phase.

****Available in Copper / Aluminium Rotor.**

****Also Available in Economy Range & Low voltage design.**



**ASM - 3 to 13
(MS / SS BODY)**

ACF SERIES...

Range : 0.25 HP to 10 HP.
Type : Centrifugal Monoblock Pump.
Del. Pipe size : 25, 40, 50, 65, 75, 100 mm.
Rpm : 2800 rpm.
Head : upto 60 mtr.
Discharge : upto 1500 lpm.
Power supply : Single & Three Phase.



**ACF - 1 to 4
SINGLE PHASE**



**ACF - 2 to 8
THREE PHASE**



**SUBMERSIBLE PUMPS
SINGLE PHASE & THREE PHASE**

V3, V4 SUBMERSIBLE SERIES... 68 mm, 74 mm, 98 mm

Range : 0.5 HP to 5 HP.
Type : Vertical Sumbersible Pump.
Del. Pipe size : 25, 32,40, 50 mm.
Rpm : 2800 rpm.
Head : upto 200 mtr.
Discharge : upto 350 lpm.
Power supply : Single and Three Phase .

****Also Available in Economy Range & Low voltage design.**

V6 SUBMERSIBLE SERIES... THREE PHASE

Range : 5 HP to 15 HP.
Type : Vertical Sumbersible Pump.
Del. Pipe size : 50, 65, 75 mm.
Rpm : 2800 rpm.
Head : upto 350 mtr.
Discharge : upto 750 lpm.
Power supply : Three Phase.

****Also Available in Low voltage design.**

OTHER PRODUCTS



**ELECTRIC MOTOR
SINGLE & THREE PHASE**



MUD PUMP



**SS MONOBLOCK
PUMP**



**POLYPROPYLENE
PUMP**



SEWAGE PUMP



CHEMICAL PUMP



DAIRY PUMP



COOLANT PUMP



BOILER PUMP



PRESSURE PUMP

MFG. BY :



AHMEDABAD - 382 430. INDIA.
E-mail: maxtronelemech@gmail.com
Website : www.ameepump.com

